Artcast®

EIFS/Stucco Adhesive Stencil Templates Specification Data Sheet



PRODUCT DESCRIPTION

Artcast® EIFS/Stucco Adhesive Stencil Templates are manufactured in the USA by Artcrete, Inc. They are manufactured from the finest quality materials and within strict standards.

PRODUCT USES

Designed for use on both commercial and residential vertical wall applications. When used in combination with an EIFS or Stucco wall finish the system creates a unique finish that simulates the look and feel of masonry.

APPLICATION INSTRUCTIONS

Field Samples

Prepare an adequate size mock-up to determine the correct placement of the stencil template. Verify compatibility of the adhesive to the base coat of the wall surface. Apply the base coat and wall finish using the same materials and application techniques indicated for project.

Artcast® EIFS/Stucco Adhesive Stencil Templates

Layout the stencil templates on the applied base coat that is dry and free from dust. Trim stencil templates to fit. Remove the backing from the adhesive side of the stencil templates. Place the stencil template against the wall surface. Use a trowel or a roller to press the stencil template against the wall surface. Check the stencil placement to insure it is plum, level and in complete contact with the surface. Please note: Areas of the stencil templates that do not adhere may leak wall finish and produce undesirable results. Apply only enough of the stencil templates that can be finished with existing manpower and weather conditions.

Wall finish

Apply wall finish in accordance with the EIFS/Stucco manufacturer's recommendations and project specifications.

PROTECTION

Protect the wall from damage caused by weather or other trades.

REMOVAL OF STENCIL TEMPLATES

The correct removal of the stencil templates is based on timing. The installing contractor should determine from the mock-up the appropriate time to remove the stencil templates from the wall surface. Temperature, humidity and the type of wall finish will affect the timing of the removal of the stencil templates. If the stencil templates are left on too long they may be hard to remove. The stencil templates may have to be trimmed from the wall finish material, depending on thickness. The wall finish shall match the approved field sample.

STORAGE

Store the stencil templates on the shipping pallet and away from excessive heat or moisture.

MAINTENANCE

See EIFS/Stucco Manufacturer's Tech Sheet.

AVAILABILITY

The stencil templates are readily available in a wide variety of patterns and thicknesses. Custom patterns are available with the proper lead time. (See Available Pattern Selection Sheet).

WARRANTY

ArtCast® EIFS/Stucco Templates are warranted to be of uniform quality within manufacturing tolerances. Since no control is exercised over its use, no warranty—expressed or implied—is made to the effects of such use. Seller and Manufacturer's obligations under this warranty are limited to refunding the purchase price of that portion of the material proven to be defective.